KS198S













Shenzhen Kings 3D Printing Technology Co., Ltd

Floor 14-15, Building 3-A, Yunzhi Science Park, Gongming Street, Guangming District, Shenzhen | China 518107

Jiangxi Kings 3D AM Tech Co., Ltd

3D Printing



Material Overview

KS198S is a white, flexible SLA resin with features of high toughness, high elasticity and soft touch. It's ideal for printing shoe prototype, rubber wrap, biomedical model and other rubber like parts.

Advantages

- High flexibility
- Good tear resistance
- Highly accurate
- Excellent white color

Ideal Applications

- Footwear
- Prototypes need rubber like material
- Soft white display models

Technical Datasheet

Liquid Properties		Optical Properties		
Appearance	White	Dp	0.125mm	[slope of cure-depth vs. In (E) curve]
Viscosity	560 cps @ 30 ℃	Ec	13.5 mJ/cm²	[critical exposure]
Density	1.1g/cm³ @ 25 ℃	Building layer thickness	0.08-0.12mm	

Mechanical Pro	perties	UV Postcure	UV Postcure
Measurement	GB Method	Value	Value
Tensile strength	GB/T 1040.1-2006	13 MPa	5 MPa
Elongation at Break	GB/T 1040.1-2006	85%	80%
Hardness, Shore A	GB/T 2411-2008	82 A	83 A
Tearing strength	GB/T 529-1999	33 kN/m	14 kN/m
Glass transition	DMA, tanθ peak	24 ℃	24 ℃

Recommended temperature for processing and storage of the above resin should be $18^{\circ}\text{C}-25^{\circ}\text{C}$.

The above data are based on our current knowledge and experience, the values of which may vary and depend on individual machine processing and post-curing practices. The safety data given in above is for information purposes only and does not constitute a legally binding MSDS. The relevant MSDS can be obtained upon request from yoursupplier or you may contact Kings 3D directly at "info@kings3dprinter.com"

Web: www.kings3dprinter.com

Email: Info@kings3dprinter.com











